

BMP21 Series PermaSleeve Heat Shrink Polyolefin Wire Marking Sleeves



Part Number: M21-375-C-342

Material: Polyolefin

Tape Color: White

For Use with Printer: BMP®21 PLUS Portable Label Printer, IDPAL™ Handheld Label Maker

Material Number: B-342

SPECIFICATIONS

| | |
|--------------------------------|-----------------------|
| Material Number | B-342 |
| Catalog Page # | 316 |
| Diameter as Supplied | 0.375 in |
| Dimensions | 0.645 in H |
| UOM | Cartridge of 7 Feet |
| Finish | Matte |
| Maximum Service Temperature °F | 275 °F |

| | |
|--------------------------------|---|
| Maximum Wire Diameter | 0.32 in |
| Maximum Wire Gauge | 4 AWG |
| Minimum Service Temperature °F | -67 °F |
| Minimum Wire Diameter | 0.125 in |
| Minimum Wire Gauge | 12 AWG |
| Product Number | 110926 |
| UPC | 662820899969 |
| Quantity per Row | 1 |
| Recovered Diameter | 0.375 in |
| Ribbon Color | Black |
| Ribbon Series | R4300 |
| Roll Length | 7 ft |
| Shrink Ratio | 3:1 |
| Sleeve Size | 0.375 in Dia x 7 ft L |
| Sleeve Size(m) | 9.5 mm Dia x 2.13 m L |
| Tape Color | White |
| Trade Name | BMP®21 PermaSleeve® |
| Web Width | 0.645 in |
| Applications | Cable & Wire Marking, Panel Labeling |
| For Use with Printer | BMP®21 PLUS Portable Label Printer, IDPAL™ Handheld Label Maker |
| Label/Media Format | Label/Media in Cartridge with Ribbon |
| Label Properties | Heat Shrink Sleeves |
| Material | Polyolefin |
| Material Properties | Flame-retardant, Heat-Shrinkable |
| Print Technology | Thermal Transfer |

| | |
|-----------------------|--|
| Resistance Properties | Chemical-Resistant, Corrosion-Resistant, Humidity-Resistant, Smear-Resistant, UV-Resistant, Weather-Resistant |
|-----------------------|--|