

# 16342-E

Decora Plus Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Smooth Face, 20 Amp, 125 Volt, Side Wire, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - Black

Leviton's line of Heavy-Duty Specification Grade receptacles are designed and manufactured to withstand the most demanding environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, etc., these Commercial Grade devices are the electrical contractor's choice for use in hotels, schools, hospitals and commercial office buildings.



**Color :**  Black


**UPC Code :** 078477805435

**Country Of Origin :** Mexico

**RoHS Compliant :** Yes

**NEMA :**  5-20R

**Available Colors :**



**Technical Information**

AC Horsepower Ratings

**At Rated Voltage :** 1 HP

Electrical Specifications

**Amperage :** 20 A

**Current Limiting :** Full Rated Current

**Dielectric Voltage :** Withstands 2000V per UL498

**Grounding :** Self-Grounding

**Pole :** 2-Pole

**Temperature Rise :** Max 30C after 250 cycles OL at 200 percent rated current

**Voltage :** 125 VAC

**Wire :** 3-Wire

Environmental Specifications

**Flammability :** Rated V-2 per UL94

**Operating Temperature :** -40C to 60C

Material Specifications

**Body Material :** Thermoplastic Nylon

**Clamp Nuts :** Zinc-Plated Steel

**Color :** Black

**Face Material :** Thermoplastic Nylon

**Ground Clips :** Brass-Plated

**Grounding Screw :** Brass 8-32

**Line Contacts :** Brass Triple-Wipe .031 Thick

**Strap Material :** Zinc-Plated Steel

**Terminal Screws :** Brass 10-32

Mechanical Specifications

**Product ID :** Ratings are permanently marked on device

**Screw Terminal Torque :** 14-18 in-lbs

**Terminal Accom. :** 14-10 AWG

**Terminal ID :** Brass-Hot, Green-Ground, Silver-Neutral

**Termination :** Side Wire

Product Features

**Brand :** Decora Plus

**Color :** Black

**Device Type :** Duplex Receptacle Outlet

**Feature 4 :** Smooth Face

**Grade :** Commercial Specification Grade

**Grounding :** Self-Grounding

**NEMA :** 5-20R

Standards and Certifications

**ANSI :** C-73

**CSA C22.2 No. 42 :** File LR-406

**NEMA :** WD-1 & WD-6

**NOM :** 057

**UL498 :** File E13399

**Warranty :** 10-Year Limited

**Patents\***

CA2483480 US6743029

MX257790 US8684771

MX321216

\*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

**SPECIFICATION SUBMITTAL**

JOB NAME:		CATALOG NUMBERS:	
<input type="text"/>		<input type="text"/>	<input type="text"/>
JOB NUMBER:		<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):  
+1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·  
FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-  
1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:  
[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

